

38MA[®]R Outdoor Unit**Heat Pump with Backup Heater****Overload Compressor**

Max 25.0 HSP

Max 33.0 HSP

Size 02 / 03 / 05 / 04 / 05 / 06

Select sizes are DASH/DMP certified based on indoor unit pairing.

Features

- 100% heating capacity at 0°F (-18°C)
Size 0-24 206/230V
- Built-in backup heater
- Available in 115V and 208/230V
- Auto restart function
- Condenser high temperature protection
- Refrigerant leakage detection
- Quiet outdoor operation, as low as 58.5 dB(A)
- Aluminum Blue Multi-splits pre-coated fins
- Piping length 80 - 324 ft.
- Cooling operating range:
-0°F - 122°F (-18° - 50°C)
- Heating operating range:
-0°F - 97°F (-18° - 37°C)
Size 0-24 206/230V
-0°F - 97°F (-18° - 37°C)
Size 0-32 050V & 30, 36 208/230V
- 10 year parts limited and 10 year compressor limited warranties in the original purchasing owner upon timely registration*

Compatibility

- 40MA[®]C High-Volt
- 40MA[®]C Cascade
- 40MA[®]D Cascade
- 40MA[®]T Four-Cascade

* If properly registered within 90 days after original installation, parts are warranted to the original purchaser for a period of 10 years. Otherwise, parts warranty is 5 years. For other applications a 7 year parts and 7 year compressor limited warranty apply. See warranty certificate for details.



Designed for versatility and year-round comfort, the 38MA[®]R achieves full heating capacity even as temperatures outside dip to 0°F with the right combination of model size and matched indoor unit. This quiet, compact heat pump pairs with a variety of indoor units for a budget-friendly and flexible solution to your most-challenged comfort needs.

Part of our Performance series, this model really delivers with features like variable speed operation for extra efficiency and reduced sound.

Performance
Series